Cloud service

Managed cloud platform or service instance.

https://docs.qintoravacloud.com/ci-classes/cloud_service/

Class policy

Class key

`cloud_service`

Parent class

base_ci

Family and category

infrastructure · cloud

CSDM domain

`foundation`

Principal class

Yes

HAM / SAM policy

— / —

Identification fields

`cloudAccountId`, `cloudResourceId`

Operational statuses

`ready`, `operational`, `degraded`, `in_maintenance`, `repair_in_progress`, `non_operational`, `disaster_recovery_standby`, `retired`

Lifecycle statuses

Class fields

`technologyType`, `number`, `cmdbClass`, `csdmDomain`, `ciStatus`, `title`, `description`, `ownerId`, `managedById`, `assignmentGroupId`, `approvalGroupId`, `companyId`, `locationId`, `dcAccountId`, `createdAt`, `updatedAt`, `environment`, `criticality`, `installDate`, `retirementDate`, `departmentId`, `costCenterId`, `discoveryManaged`, `discoverySourceId`, `ireRuleId`, `lastDiscovered`, `parentLocationCiId`

Parent required

No

Allowed parent classes

cloud_data_center

Create or reconcile a CI

In CMDB, select the class, fill its identity fields, then verify the record's class, source and relationships after save or ingestion. For a possible duplicate, compare the source identity and

class identifiers before changing the reconciliation rule. See Model and reconcile configuration items.