Data center zone

Resilience, security, or power zone within a data-center room.

https://docs.qintoravacloud.com/ci-classes/data_center_zone/

Class policy

Class key

`data_center_zone`

Parent class

data_center_room

Family and category

facility · data_center

CSDM domain

`foundation`

Principal class

No

HAM / SAM policy

— / —

Identification fields

`parentLocationCiId`, `zoneCode`

Operational statuses

`planned`, `commissioning`, `operational`, `degraded`, `capacity_constrained`, `restricted_access`, `in_maintenance`, `non_operational`, `decommissioning`, `decommissioned`

Lifecycle statuses

Class fields

`technologyType`, `number`, `cmdbClass`, `csdmDomain`, `ciStatus`, `title`, `description`, `ownerId`, `managedById`, `assignmentGroupId`, `approvalGroupId`, `companyId`, `locationId`, `dcAccountId`, `createdAt`, `updatedAt`, `parentLocationCiId`, `locationCode`, `zoneCode`, `powerCapacityKw`, `coolingCapacityKw`, `rackCapacity`, `discoveryManaged`, `discoverySourceId`, `ireRuleId`, `lastDiscovered`

Parent required

Yes

Allowed parent classes

data_center_room

Create or reconcile a CI

In CMDB, select the class, fill its identity fields, then verify the record's class, source and relationships after save or ingestion. For a possible duplicate, compare the source identity and

class identifiers before changing the reconciliation rule. See Model and reconcile configuration items.