Endpoint

Base class for user computing devices.

https://docs.qintoravacloud.com/ci-classes/endpoint/

Class policy

Class key

endpoint

Parent class

base_ci

Family and category

hardware · endpoint

CSDM domain

foundation

Principal class

Yes

HAM / SAM policy

HAM / SAM

Identification fields

serialNumber, assetTag

Operational statuses

ready, operational, degraded, in_maintenance, repair_in_progress, non_operational, disaster_recovery_standby, retired

Lifecycle statuses

on_order, in_stock, in_transit, installed, in_maintenance, pending_retirement, retired, disposed

Class fields

technologyType, number, cmdbClass, csdmDomain, ciStatus, title, description, ownerId, managedById, assignmentGroupId, approvalGroupId, companyId, locationId, dcAccountId, createdAt, updatedAt, installStatus, stockroomId, assetTag, serialNumber, manufacturer, model, purchaseDate, installDate, warrantyExpiration, retirementDate, assetRecordId, assetLifecycleState, departmentId, costCenterId, discoveryManaged, discoverySourceId, ireRuleId, lastDiscovered, hostname, fqdn, operatingSystem, osVersion, cpuCount, memoryGb, storageGb, ipAddress, macAddress, virtualizationType, endpointType, assignedUserId, encryptionStatus, dcAccountId

Parent required

No

Allowed parent classes

See the CI form and relationship policy

Create or reconcile a CI

In CMDB, select the class, fill its identity fields, then verify the record's class, source and relationships after save or ingestion. For a possible duplicate, compare the source identity and class identifiers before changing the reconciliation rule. See Model and reconcile configuration items.