Load balancer

Physical, virtual, or cloud load-balancing service.

https://docs.qintoravacloud.com/ci-classes/load_balancer/

Class policy

Class key

`load_balancer`

Parent class

network

Family and category

infrastructure · network

CSDM domain

`foundation`

Principal class

Yes

HAM / SAM policy

— / —

Identification fields

`cloudResourceId`, `fqdn`, `managementIp`

Operational statuses

`ready`, `operational`, `degraded`, `in_maintenance`, `repair_in_progress`, `non_operational`, `disaster_recovery_standby`, `retired`

Lifecycle statuses

Class fields

`technologyType`, `number`, `cmdbClass`, `csdmDomain`, `ciStatus`, `title`, `description`, `ownerId`, `managedById`, `assignmentGroupId`, `approvalGroupId`, `companyId`, `locationId`, `dcAccountId`, `createdAt`, `updatedAt`, `environment`, `criticality`, `installDate`, `retirementDate`, `departmentId`, `costCenterId`, `discoveryManaged`, `discoverySourceId`, `ireRuleId`, `lastDiscovered`, `hostname`, `fqdn`, `ipAddress`, `macAddress`, `networkDeviceType`, `managementIp`, `firmwareVersion`, `networkZone`, `rackLocation`, `portCount`

Parent required

No

Allowed parent classes

See the CI form and relationship policy

Create or reconcile a CI

In CMDB, select the class, fill its identity fields, then verify the record's class, source and relationships after save or ingestion. For a possible duplicate, compare the source identity and

class identifiers before changing the reconciliation rule. See Model and reconcile configuration items.