Directory source · Other HTTPS provisioning source

Configure a read-only source and preview identity matching before apply.

https://docs.qintoravacloud.com/integrations/directory-source/custom/

Connection and scope

Configure the published read-only tenant export endpoint; there is no universal worker URL. JSON/CSV field names must match the report schema. Secret JSON: accessToken/token; or username/password for Basic; or clientId/clientSecret/tokenUrl for OAuth client credentials. OAuth token origin must equal the separately configured token origin. Import preview validates the actual schema before writes.

Transport

`export`

External ID

`id`

Default coalescing path

`email`

Provider fields

Key	Label	Example
`path`	Authenticated export/report path	`Enter the published tenant-specific path`
`collectionPath`	JSON collection path (blank for root array)	`Report_Entry`
`nextPath`	JSON next-page URL property (optional)	`next`
`format`	Response format	`json or csv`

Default mapping

Source	Target	Transform
`firstName`	`firstName`	`text`
`lastName`	`lastName`	`text`
`email`	`email`	`lower`
`email`	`username`	`lower`

Source	Target	Transform
`id`	`ldapCorrelationId`	`text`

Verify and troubleshoot

Preview, apply, and diagnose a directory import. Verify the immutable key, existing-account match, complete pagination and disable thresholds before applying.